

## H.F. ACID

DESCRIPTION	H.F. ACID offers extra economy for the removal of milkstone and other mineral deposits from food processing equipment. H.F. ACID may be used in all types of applications from hand scrubbing to power spray, soak, foam and circulation cleaning.
DIRECTIONS	Usage varies with the amount of film and residue, but usually 1/2 oz. per gallon of water for all applications except foaming. For foaming, use 1 to 4 oz. per gallon of water. Always follow with a potable water rinse after use. Consult your representative for specific applications and concentrations in your operation.
FEATURES	Authorized by the USDA for use in federally inspected meat and poultry plants
SAFETY INFORMATION	UTILIZE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT AS PER SDS. HANDLE AND STORE AS INDICATED ON PRODUCT LABEL.

IF ON SKIN: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention. Wash clothes before reusing.

IF IN EYES: In case of contact, immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

IF SWALLOWED: Drink large quantities of milk or water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.

IF INHALED: Immediately move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get immediate medical attention.

Consult your Safety Data Sheet for additional safety information.

FOR INDUSTRIAL USE ONLY.

**DANGER!**

CORROSIVE. CONTAINS PHOSPHORIC ACID.

NEVER MIX THIS PRODUCT WITH ANY PRODUCT CONTAINING  
CHLORINE, AMMONIA, OR WITH ALKALINE PRODUCTS.