

H.T. SPECIAL

DESCRIPTION	H.T. SPECIAL is designed for high temperature recirculation cleaning. In combination with ALKA-CLEAN ADDITIVE 1500™ or ALKA-CLEAN ADDITIVE 2000™, a powerful cleaning system is achieved for HTST units, evaporators or boil-outs.
DIRECTIONS	<p>H.T. SPECIAL is designed for high temperature recirculation cleaning.</p> <p>Procedure: Soak, circulation, spray and boil-out cleaning. After cleaning, post-rinse with potable water. Sanitize as required.</p> <p>Concentration: 0.5 oz. to 8.0 oz. per gallon of water depending on soil load and method of cleaning. Consult your DeLaval rep for specific concentrations.</p> <p>Temperature: 120° to 200°F.</p> <p>Cleaning Time: 15 minutes to 2 hours or as required by soil load and method of cleaning.</p>
SAFETY INFORMATION	<p>UTILIZE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT AS PER SDS.</p> <p>HANDLE AND STORE AS INDICATED ON PRODUCT LABEL.</p>

IF ON SKIN: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation persists. Wash clothes before reusing.

IF IN EYES: In case of contact, immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

IF SWALLOWED: Drink large quantities of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.

IF INHALED: Immediately move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get immediate medical attention.

Consult your Safety Data Sheet for additional safety information.