

TROLLEY LUBE T Conveyor Chain Lubricant

DESCRIPTION TROLLEY LUBE T is designed for lubrication of trolleys in meat plants to reduce wear on trolleys and conveying equipment and to aid in mechanical or manual movement of the carcass. It is also used to aid in the prevention of rust or other corrosion, which is often encountered from moisture or salt in coolers. It is an off-white to tan, clear liquid containing food grade oils and pressure lubricants.

DIRECTIONS TROLLEY LUBE T is normally applied by floating on top of a water layer in a suitable dip tank. This tank should be equipped with a drain valve near the bottom of the tank in order to drain any excess water in the tank and also for the removal on any sediment.

For oiling, the oil layer should be 2 to 10 inches in thickness, and the temperature should be maintained between 140° to 170°F to allow proper penetration into the pores of the metal. The temperature and thickness of the oil layer can also be used to control the optimum amount of oil needed to give proper lubrication and prevent rusting.

Prior to oiling, trolleys must be thoroughly cleaned and de-rusted with the proper DeLaval product. After washing the trolleys, rinse with hot water at high pressure prior to the oil dip.

FEATURE Authorized by USDA for use in federally inspected meat and poultry plants

SAFETY INFORMATION UTILIZE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT AS PER SDS.
HANDLE AND STORE AS INDICATED ON PRODUCT LABEL.

IF SWALLOWED: Drink large quantities of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Consult your Safety Data Sheet for additional safety information.