

WWT 6100S

Coagulant for Waste Water Treatment

DESCRIPTION WWT 6100S™ is an organic/inorganic cationic coagulant blend designed to break oil-in-water emulsions.

DIRECTIONS Add at 20 ppm - 200 ppm to waste process water and allow to thoroughly mix for a minimum of 30 seconds. For best results, waste process water should be at a pH between 6 and 9. It is recommended that this product be used in conjunction with a flocculant added at least 30 seconds after the **WWT 6100S** has been added. **WWT 6100S** may be added neat or in a 10:1 water to product dilution.

Do not reclaim treated waste water. Treated effluent should be discharged to local waste treatment facility.

SAFETY INFORMATION **UTILIZE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT AS PER SDS. HANDLE AND STORE AS INDICATED ON PRODUCT LABEL.**

IF ON SKIN: Wash off immediately with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation persists. Wash clothes before reuse.

IF IN EYES: Rinse thoroughly with plenty of water, including under the eyelids, for at least 15 minutes. Get medical attention if irritation persists.

IF SWALLOWED: DO NOT induce vomiting. Drink large amounts of milk or water. **Call a physician or Poison Control Center immediately.** Never give anything by mouth to an unconscious person.

IF INHALED: Move to fresh air. If breathing is difficult, or irritation persists, get medical attention.

Consult your Safety Data Sheet for additional safety information.