

## WWT C40G

### G.R.A.S. Waste Water Flocculant

**DESCRIPTION** WWT C40G™ is a waste water flocculant that may be used as a waste process water flocculant and/or a sludge thickening agent.

**DIRECTIONS** Thoroughly mix product with a minimum of 200 parts of water to 1 part product (0.5%). Add diluted product directly to waste process water at a dose of 2 to 50 ppm as product. Product can also be used as a sludge conditioning agent at doses up to 200 ppm as product.

Consult your DeLaval representative for specific dosage recommendations.

**SAFETY INFORMATION** **UTILIZE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT AS PER SDS. HANDLE AND STORE AS INDICATED ON PRODUCT LABEL.**

**IF ON SKIN:** Wash off immediately with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation persists. Wash clothes before reuse.

**IF IN EYES:** Rinse thoroughly with plenty of water, including under the eyelids, for at least 15 minutes. Get medical attention if irritation persists.

**IF SWALLOWED:** DO NOT induce vomiting. Drink a small amount of water. **Call a physician or Poison Control Center immediately.** Never give anything by mouth to an unconscious person.

**IF INHALED:** Move to fresh air. If breathing is difficult, or irritation persists, get medical attention.

Consult your Safety Data Sheet for additional safety information.