

HOT TANK #2

DESCRIPTION HOT TANK #2 is a phosphated, granulated, highly alkaline cleaning compound containing caustic soda. It offers top efficiency in the removal of heavy soils for all types of food plant cleaning. This product is low foaming for a high rate of emulsification of fats and greases. It also will remove and dissolve proteins. It has a long life for soak tanks and rinses well. Do not use on any soft metal including aluminum or on painted surfaces of any kind.

DIRECTIONS HOT TANK #2 may be used for circulation and soak cleaning.

Concentration: 2 to 4 oz. per gallon of water. Usage amounts will vary with type and degree of soil.

Temperature: 160° to 190°F.

Consult your representative for specific applications and concentrations in your operation.

FEATURES Authorized by the USDA for use in federally inspected meat and poultry plants

SAFETY INFORMATION UTILIZE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT AS PER SDS.
HANDLE AND STORE AS INDICATED ON PRODUCT LABEL.

IF ON SKIN: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothes before reusing.

IF IN EYES: In case of contact, immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

IF SWALLOWED: Drink large quantities of milk or water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.

IF INHALED: Immediately move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get immediate medical attention.

Consult your Safety Data Sheet for additional safety information.

FOR INDUSTRIAL USE ONLY.

DANGER!

CORROSIVE. CONTAINS CAUSTIC SODA.